



6DC6

6DC6

SEMIREMOTE-CUTOFF PENTODE

MINIATURE TYPE

GENERAL DATA

Electrical:

Heater, for Unipotential Cathode:

Voltage 6.3 ac or dc volts

Current 0.3 amp

Direct Interelectrode Capacitances (No external shield):

Grid No.1 to plate . . . 0.02 max. $\mu\mu\text{f}$ Input 6.5 $\mu\mu\text{f}$ Output 2 $\mu\mu\text{f}$

Mechanical:

Maximum Overall Length 2-1/8"

Maximum Seated Length 1-7/8"

Length, Base Seat to Bulb Top

(Excluding tip) 1-1/2" $\pm 3/32$ "

Maximum Diameter 3/4"

Bulb T-5-1/2

Base Small-Button Miniature 7-Pin (JETEC No. E7-1)


Basing Designation for BOTTOM VIEW 70M

Pin 1-Grid No.1

Pin 2-Cathode

Pin 3-Heater

Pin 4-Heater



Pin 5-Plate

Pin 6-Grid No.2

Pin 7-Grid No.3,
Internal
ShieldAMPLIFIER - Class A₁

Maximum Ratings, Design-Center Values:

PLATE VOLTAGE 300 max. volts

GRID-No.3 (SUPPRESSOR) VOLTAGE 0 max. volts

GRID-No.2 SUPPLY VOLTAGE 300 max. volts

GRID-No.2 (SCREEN) VOLTAGE See Rating Curve at
front of this Section

GRID-No.1 (CONTROL-GRID) VOLTAGE:

Positive bias value 0 max. volts

PLATE DISSIPATION 2 max. watts

GRID-No.2 INPUT 0.5 max. watt

PEAK HEATER-CATHODE VOLTAGE:

Heater negative with respect to cathode . . . 200 max. volts

Heater positive with respect to cathode . . . 200[▲] max. volts

Typical Operation and Characteristics:

Plate Supply Voltage 200 volts

Grid No.3 Connected to cathode at socket

Grid-No.2 Voltage 150 volts

Cathode-Bias Resistor 180 ohms

Plate Resistance (Approx.) 0.5 megohm

[▲] The dc component must not exceed 100 volts.

JUNE 14, 1954

TUBE DIVISION

TENTATIVE DATA

RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY

6DC6



6DC6

SEMIREMOTE-CUTOFF PENTODE

Transconductance	5500	μ mhos
Grid-No.1 Voltage (Approx.) for transconductance of 50 μ mhos	-12.5	volts
Plate Current	9	ma
Grid-No.2 Current	3	ma

Maximum Circuit Values (For maximum rated conditions):

Grid-No.1-Circuit Resistance:

For fixed-bias operation	0.25 max. megohm
For cathode-bias operation	1.0 max. megohm

JUNE 14, 1954

TUBE DIVISION

TENTATIVE DATA


RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY



6DC6

6DC6

AVERAGE PLATE CHARACTERISTICS



ELECTRON TUBE DIVISION
RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY


92CM-8330RI

6DC6



6DC6

AVERAGE CHARACTERISTICS



ELECTRON TUBE DIVISION
 RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY


92CM-8337



6DC6

6DC6

AVERAGE CHARACTERISTICS



JUNE 15, 1954

TUBE DIVISION
RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY


92CM-8338

6DC6



6DC6

AVERAGE CHARACTERISTICS



JUNE 15, 1954

TUBE DIVISION
 RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY

92CM-8336